

## PART III INDEX

- Activity coefficients, at infinite dilution, 808
- Additives, effect on solubility of corrosion products in bismuth, 727
- Alloy steel, 743
- Annual aqueous processing costs vs plant throughput, 881
- Annual fluoride volatility processing cost vs plant throughput, 880
- Anti-oxidant, 722
- Argonne National Laboratory, 821
- Babcock and Wilcox Company, 704, 866n
- Basis of nuclear calculations, 901
- Bearing materials, 771
- Bellows, 850
- Beryllium, 770
- Beryllium oxide, 706
- Bismuth, 703
  - inventory, 877
  - charges, 907
  - physical properties of, 838
  - preparation, 855
  - properties, 731
  - solubilities in, 723
- Blanket, 707
  - chemical processing, 828
  - gas, 855
  - slurry, thorium bismuthide, 734
  - slurry-to-graphite volume ratio, 867
  - thickness, 867
- Breeding, 714, 717
  - gain vs bismuth-to-carbon volume ratio in core, 868
  - ratio, higher uranium isotopes, 886
  - vs slurry-to-carbon volume ratio in blanket, 868
- Brookhaven National Laboratory, 866n
  - work at, 703
- Buckling, of graphite-moderated LMFR cores, 716
- Capital investment, fixed charges on, 920
- Capsule cooling, 896
- Centrifugal pump, canned-motor, 847
- Charging procedures, 855
- Chemical processing, 703, 791, 897
  - blanket power, 880
  - costs, 881, 909
    - vs blanket power, 882
    - cycle selection of, 915
    - economics of, 829
- Chemistry, of equilibrium distribution, 802
- Cleaning of equipment, 852
- Compact arrangements, 833
- Component design, 843
- Conditioning operation, 856
- Container material, 744
- Containment and safety requirements, 834
- Control, 718, 896
- Control rods, 886
- Conversion ratio vs diameter, 904
- Core, 707, 715
- Core fuel composition, 722
- Corrosion, 703
  - effect of velocity on, 767
  - inhibitor, 722
- Countercurrent Bi-Na heat exchanger, typical conditions in, 844
- Cr, effect on the solubility of Fe in Bi, 730
- Critical mass, 717
- Criticality calculations, two-fluid LMFR, 869
- Cross sections, 711
- Delayed neutron emitter concentration, 718
- Design methods, 835
- Design parameters, study of, 867
- Dissolution, of Fe into Bi (plus additives), 750
- Dump tank heating and cooling, 894
- Economic optimization, 873, 905
  - results of, 909
- Economics, 920

- Electromagnetic flowmeter, 861
- Electromagnetic pumps, 844
  - characteristics, 845
  - efficiency, 845
- End blanket effects, 869
- Energy costs, summary, 921
- Engineering design, 832 ff
- Equilibrium distribution, 802
- Equipment charging, 855
- Equipment for FPV removal, design of, 800
- Extraction columns, 818
  - design of, 817
- Fission product graphite reactions, 778
- Fission product groups, statistics on, 814
- Fission product poisons, 887
  - in the blanket, 871
  - in the core, 873
- Fission product solubility, 725
- Fission products, effect on solubility of uranium-bismuth, 727
  - fused salt soluble, 792
  - gaseous, 791
  - nonvolatile elements, 791
  - poison level after startup vs time of operation, 795
- Flow measurement, 861
- Fluid and solid fuel reactors,
  - comparison of, 704
- Fluid fuel, 703
- Fluoride volatility process for fission products, 821
- FPN, 791
  - concentrations, after 400 days of operation, 823
  - fission products removal, flowsheet, 826
  - poisoning, characteristics of, 823
  - removal, for the fused chloride process, 825
  - removal process, for the fluoride volatility process, 827
- FPS, 791
  - and Zr fission products, flowsheet for removal from LMFR fuel, 813
  - energy release from, 821
  - removal column, with two equilibrium stages, typical concentrations in, 815
  - removal process, 812
    - transfer and distribution data, thermodynamics of, 804
- FPV, 791
- Fuel burnup, 879
  - costs, 909
- Fuel costs, 921
  - summary of, 928
- Fuel inventory, 877
  - charges, 908
- Fuel preparation, 731
- Fuel solution, reaction with air, 732
- Fuel stability, 731
- Fused chloride salt process, 801
  - pilot plant for, 820
- Gas solubilities in bismuth, 731
- Geometry effects, 886
- Graphite, 706, 744, 774
  - bismuth permeation and diffusion into, 782 ff
  - general physical properties, 776
  - radiation effects on, 779
  - reactions, 775
  - system, 852
  - zirconium and titanium reactions with, 778
- Graphite-to-metal seals, 775
- Head end processing, bismuthide slurry, 898
- Heat exchange, 703
- Heat exchanger, 704, 725
  - design, 843
    - comparison of coolants at fixed linear velocity, 843
    - comparison of coolants when number of tubes in parallel is fixed, 842
- Heat generation by fission products, 820
- Heat generation rates, 827
- Heat transfer, 836
- Heating equipment, 852
- High-temperature radiography, 857
- High velocity loops, results from, 762
  - pump test loop, 761
  - tests, 759
- Homogenous systems, 720
- In-line bismuth sampler, 857
  - capsule experiments, 797, 799
- Instrumentation, 858, 896

- Insulation, 852  
Intermediate inert gas system, 895
- LAMPRE, 706, 942  
control, 943  
core, 142  
illustrated, 944  
reflector, 943
- Leak testing, 854
- Liquid bismuth loop, 853
- Liquid level measurement, 858
- Liquid metal fuel reactor: *see* LMFR
- Liquid metal fuel-gas cooled reactor, 930
- Liquid metal UO<sub>2</sub> slurry fuel, 930
- Liquid metal-uranium oxide slurry reactors, 944
- LMF-GCR, fuel system, 935  
model section of nuclear core element, 934  
nuclear power station, artist's concept, 932  
plant capital and power cost, 939  
plant operation and maintenance, 938  
reactor materials, 938  
reference design characteristics, 931  
summary of design parameters, 936
- LMFR, (Liquid Metal Fuel Reactor),  
advantages, 705  
classification of, 707  
comparison with aqueous systems, 705  
design study, 866 ff  
designs, single fluid, 866  
designs, two-fluid, 866  
disadvantages, 705  
externally cooled, 832  
externally cooled compact arrangement, 833  
externally cooled open arrangement, 835  
general characteristics, 704 ff  
general discussion, 703 ff  
heat transfer for, 841  
intermediate system, 892  
internally cooled, 832  
kinetics, 719  
materials, 743  
parameters, 711  
primary system, 891  
program, general discussion, 708  
schematic diagram, 708  
single fluid, 707  
single-region, externally cooled, 918  
statics, 715  
two-fluid, 707  
two-region, externally cooled, 870  
types, 706
- LMFR-6: capsulate loop plant elevation, 891  
capsulate loop plant conception layout, 890
- Loop method, open, 719
- Losses, of uranium from bismuth by reaction with container materials, 732
- Low-chrome steels, 854
- Magnesium, 725  
as an oxygen getter, 722  
concentration in exit fuel, effect on compositions of exit streams from FPS removal column, 819
- Maintenance, 897  
and repair provisions, 836
- Mass of U<sup>235</sup> vs reactor operating time, 916
- Mass transfer, 740  
corrosion, 728  
effect of velocity on, 767
- Materials of construction, 743
- Mechanical pumps, 846
- Metal systems, joints, 851
- Metallurgy, 743
- Moderator, 744
- Molten plutonium fuel reactor, 930, 939  
basic components, 940
- Molten plutonium fuels, 940
- Molybdenum, 725, 771  
removal, 826
- Neutron age, 713
- Neutron balance, 888  
of Th<sup>232</sup>, U<sup>233</sup> breeder, 718
- Neutron economy, 704
- Neutron losses vs reactor operating time, 916
- NFPN, 791  
fission-product removal, 899  
removal by zinc drossing, chemistry of, 824

- Noble fission product removal, 823  
Nonferrous metals, 770  
Nuclear aspects of coolants, 837  
Nuclear calculations, 874  
    for various power splits, results of, 876  
    results, 903  
Nuclear properties of various reactor coolants, 839
- Off-gas system, 899  
Open arrangements, 834  
Orifice, 861  
Oxidation, concurrent, of U, Zr, and Mg from Bi, 733
- Pa<sup>233</sup>, 713  
Parametric study, 901  
Pilot plant equilibrium experiments, 809  
Piping, 849  
Plant arrangement, 889  
Plutonium, 725  
Polonium, 705  
    removal, 826  
Power level, in the blanket, 871  
Precipitation, of Fe-Cr alloy in high velocity cold leg test section, 763  
Preheating, 855  
Pressure measurement, 859  
Pressure transmitters, 860  
Primary inert gas system, 895  
Process control, of fused chloride process, 817  
Process design, data for, 809  
Processing to reduce radiation hazard, 820  
Protactinium losses, 886  
Pumping power requirements, 840  
Pumps, 843  
Pyrometallurgical processing, 734
- Rapid oxidation, 767  
Rates of precipitation, 750  
Raw water system, 896  
Reaction rates, 811  
Reactivity effects, 713  
Reactor and pressure vessel assembly, 933  
    cell cooling, 895  
    cost, 906  
    heating and cooling system, 893  
    room cooling, 896  
    savings vs reflector thickness, 907  
Reduction of UO<sub>2</sub> by Mg in Bi, 733  
Reference design, selection of, 883, 911  
specifications, 887, 918  
Reflector, 715  
Reflector savings, of U<sup>235</sup>-Bi cores moderated by graphite, 716  
Relative cost vs slurry-to-graphite ratio, 910  
    vs thorium concentration, 910  
Relative fuel costs vs blanket power, 882, 883  
Repair techniques, 858  
Results of optimization, 881
- Salt corrosion, 773  
Salts, 730  
Samarium in the blanket, 873  
Sampling, 856  
Shield cooling, 895  
Shielding, 719  
Sight ports, 852  
Single-fluid LMFR, critical fuel concentration vs thorium concentration, 905  
    critical fuel concentration vs slurry-to-graphite volume ratio, 905  
    conversion ratio vs slurry-to-graphite ratio, 904  
    relative energy costs, 912  
    relative fuel costs including chemical processing, 914  
    summary of capital investment, 926  
    summary of direct construction costs, 922  
Single-fluid nuclear calculations, summary, 902  
Single-fluid reactor cost, estimated, 907  
    design, 900  
Slurries, engineering studies of, 738  
    thorium compound, 741  
Slurry behavior, under conditions of reactor blanket operation, 739  
Slurry preparation, electrolytic method, 736  
Solubility, mutual, of uranium zirconium in bismuth, 727  
    of combination of elements in bismuth, 726  
    of corrosion products in bismuth, 726

- of Fe, Cr, Ni, and Mn in bismuth, 728
- of Fe in Bi alloys, 745
- of fission products in bismuth, 726
- of plutonium and uranium in bismuth, 724
- of steel components and inhibiting additives in bismuth, 744
- of titanium in bismuth, 728
- of uranium and thorium in bismuth, 724
- of uranium in bismuth, 729
- Solutes, distribution between  $MgCl_2$ - $NaCl$ - $KCl$ , 805
- Solution properties, 731
- Solution rate tests, 749
- Solutions, physical properties of, 731
- Stainless steels, 743, 854
- Startup heating system, 894
- Static tests, 744
- Steel composition and heat treatment, effect of, 748
- Steels, corrosion testing on, 751
  - radiation effects on, 768
  - reactions with Bi solutions, 746
- Study groups, work of, 704
- Surface reactions, 745
  - of zirconium, titanium, and magnesium, 746
- System design, 888
- System preparation, 852
  
- Tantalum, 770
- Temperature measurement, 862
- Ternary salt, 803
- Theory and experiment, comparison of, 805
- Thermal breeder, 711
- Thermal convection loop, 753
  - data, summary, 754
  - tests at BNL, 751
- Thief-type sampler, 856
- Thorium<sup>232</sup>, 722
- Thorium, 706, 725
  - amortization charges, 879
  - bismuth blanket, preparation, 736 ff
  - bismuthide, chemical composition, 734
    - crystal chemistry, 734
  - burnup, 879
    - costs, 909
  - oxide, 741
- Time study, 911
  - results of, 915
- Turbine generator plant, 898
- Two-fluid LMFR, chemical processing
  - costs, 884
  - inventory volumes in, 879
  - summary of direct construction costs, 924
- Two-fluid reactor, design, 866
  - general description, 866
  - general specifications, 867
- Typical reactor coolants, physical properties, 840
  
- $U^{233}$ , 706
- $U^{235}$ , 706
- $U^{238}$ , 706
- Unit energy costs, 929
- Uranium, 703, 723
- Uranium-graphite reactions, 775
- Uranium removal column, with four removal stages, 816
- U-Zr-Bi ternary system: liquidus curves at 375, 400, and 425°C, 729
  
- Values of  $\mu$ , the gamma absorption coefficient, 839
- Valves, 848
- Variable fuel cost, 916
- Volatile fission product removal, 795
  
- Xenon, and iodine adsorption on graphite and steel, 796
  - and iodine removal, 795
  - concentration, changes in, 718
  - in the blanket, 872
  
- Zirconium, 725
  - as a corrosion inhibitor, 722