

PART III INDEX

- Activity coefficients, at infinite dilution, 808
- Additives, effect on solubility of corrosion products in bismuth, 727
- Alloy steel, 743
- Annual aqueous processing costs vs plant throughput, 881
- Annual fluoride volatility processing cost vs plant throughput, 880
- Anti-oxidant, 722
- Argonne National Laboratory, 821
- Babcock and Wilcox Company, 704, 866n
- Basis of nuclear calculations, 901
- Bearing materials, 771
- Bellows, 850
- Beryllium, 770
- Beryllium oxide, 706
- Bismuth, 703
 - inventory, 877
 - charges, 907
 - physical properties of, 838
 - preparation, 855
 - properties, 731
 - solubilities in, 723
- Blanket, 707
 - chemical processing, 828
 - gas, 855
 - slurry, thorium bismuthide, 734
 - slurry-to-graphite volume ratio, 867
 - thickness, 867
- Breeding, 714, 717
 - gain vs bismuth-to-carbon volume ratio in core, 868
 - ratio, higher uranium isotopes, 886
 - vs slurry-to-carbon volume ratio in blanket, 868
- Brookhaven National Laboratory, 866n
 - work at, 703
- Buckling, of graphite-moderated LMFR cores, 716
- Capital investment, fixed charges on, 920
- Capsule cooling, 896
- Centrifugal pump, canned-motor, 847
- Charging procedures, 855
- Chemical processing, 703, 791, 897
 - blanket power, 880
 - costs, 881, 909
 - vs blanket power, 882
 - cycle selection of, 915
 - economics of, 829
- Chemistry, of equilibrium distribution, 802
- Cleaning of equipment, 852
- Compact arrangements, 833
- Component design, 843
- Conditioning operation, 856
- Container material, 744
- Containment and safety requirements, 834
- Control, 718, 896
- Control rods, 886
- Conversion ratio vs diameter, 904
- Core, 707, 715
- Core fuel composition, 722
- Corrosion, 703
 - effect of velocity on, 767
 - inhibitor, 722
- Countercurrent Bi-Na heat exchanger, typical conditions in, 844
- Cr, effect on the solubility of Fe in Bi, 730
- Critical mass, 717
- Criticality calculations, two-fluid LMFR, 869
- Cross sections, 711
- Delayed neutron emitter concentration, 718
- Design methods, 835
- Design parameters, study of, 867
- Dissolution, of Fe into Bi (plus additives), 750
- Dump tank heating and cooling, 894
- Economic optimization, 873, 905
 - results of, 909
- Economics, 920

- Electromagnetic flowmeter, 861
- Electromagnetic pumps, 844
 - characteristics, 845
 - efficiency, 845
- End blanket effects, 869
- Energy costs, summary, 921
- Engineering design, 832 ff
- Equilibrium distribution, 802
- Equipment charging, 855
- Equipment for FPV removal, design of, 800
- Extraction columns, 818
 - design of, 817
- Fission product graphite reactions, 778
- Fission product groups, statistics on, 814
- Fission product poisons, 887
 - in the blanket, 871
 - in the core, 873
- Fission product solubility, 725
- Fission products, effect on solubility of uranium-bismuth, 727
 - fused salt soluble, 792
 - gaseous, 791
 - nonvolatile elements, 791
 - poison level after startup vs time of operation, 795
- Flow measurement, 861
- Fluid and solid fuel reactors,
 - comparison of, 704
- Fluid fuel, 703
- Fluoride volatility process for fission products, 821
- FPN, 791
 - concentrations, after 400 days of operation, 823
 - fission products removal, flowsheet, 826
 - poisoning, characteristics of, 823
 - removal, for the fused chloride process, 825
 - removal process, for the fluoride volatility process, 827
- FPS, 791
 - and Zr fission products, flowsheet for removal from LMFR fuel, 813
 - energy release from, 821
 - removal column, with two equilibrium stages, typical concentrations in, 815
 - removal process, 812
 - transfer and distribution data, thermodynamics of, 804
- FPV, 791
- Fuel burnup, 879
 - costs, 909
- Fuel costs, 921
 - summary of, 928
- Fuel inventory, 877
 - charges, 908
- Fuel preparation, 731
- Fuel solution, reaction with air, 732
- Fuel stability, 731
- Fused chloride salt process, 801
 - pilot plant for, 820
- Gas solubilities in bismuth, 731
- Geometry effects, 886
- Graphite, 706, 744, 774
 - bismuth permeation and diffusion into, 782 ff
 - general physical properties, 776
 - radiation effects on, 779
 - reactions, 775
 - system, 852
 - zirconium and titanium reactions with, 778
- Graphite-to-metal seals, 775
- Head end processing, bismuthide slurry, 898
- Heat exchange, 703
- Heat exchanger, 704, 725
 - design, 843
 - comparison of coolants at fixed linear velocity, 843
 - comparison of coolants when number of tubes in parallel is fixed, 842
- Heat generation by fission products, 820
- Heat generation rates, 827
- Heat transfer, 836
- Heating equipment, 852
- High-temperature radiography, 857
- High velocity loops, results from, 762
 - pump test loop, 761
 - tests, 759
- Homogenous systems, 720
- In-line bismuth sampler, 857
 - capsule experiments, 797, 799
- Instrumentation, 858, 896

- Insulation, 852
 Intermediate inert gas system, 895
- LAMPRE, 706, 942
 control, 943
 core, 142
 illustrated, 944
 reflector, 943
- Leak testing, 854
- Liquid bismuth loop, 853
- Liquid level measurement, 858
- Liquid metal fuel reactor: *see* LMFR
- Liquid metal fuel-gas cooled reactor, 930
- Liquid metal UO₂ slurry fuel, 930
- Liquid metal-uranium oxide slurry reactors, 944
- LMF-GCR, fuel system, 935
 model section of nuclear core element, 934
 nuclear power station, artist's concept, 932
 plant capital and power cost, 939
 plant operation and maintenance, 938
 reactor materials, 938
 reference design characteristics, 931
 summary of design parameters, 936
- LMFR, (Liquid Metal Fuel Reactor),
 advantages, 705
 classification of, 707
 comparison with aqueous systems, 705
 design study, 866 ff
 designs, single fluid, 866
 designs, two-fluid, 866
 disadvantages, 705
 externally cooled, 832
 externally cooled compact arrangement, 833
 externally cooled open arrangement, 835
 general characteristics, 704 ff
 general discussion, 703 ff
 heat transfer for, 841
 intermediate system, 892
 internally cooled, 832
 kinetics, 719
 materials, 743
 parameters, 711
 primary system, 891
 program, general discussion, 708
 schematic diagram, 708
 single fluid, 707
 single-region, externally cooled, 918
 statics, 715
 two-fluid, 707
 two-region, externally cooled, 870
 types, 706
- LMFR-6: capsule loop plant elevation, 891
 capsule loop plant conception layout, 890
- Loop method, open, 719
- Losses, of uranium from bismuth by reaction with container materials, 732
- Low-chrome steels, 854
- Magnesium, 725
 as an oxygen getter, 722
 concentration in exit fuel, effect on compositions of exit streams from FPS removal column, 819
- Maintenance, 897
 and repair provisions, 836
- Mass of U²³⁵ vs reactor operating time, 916
- Mass transfer, 740
 corrosion, 728
 effect of velocity on, 767
- Materials of construction, 743
- Mechanical pumps, 846
- Metal systems, joints, 851
- Metallurgy, 743
- Moderator, 744
- Molten plutonium fuel reactor, 930, 939
 basic components, 940
- Molten plutonium fuels, 940
- Molybdenum, 725, 771
 removal, 826
- Neutron age, 713
- Neutron balance, 888
 of Th²³², U²³³ breeder, 718
- Neutron economy, 704
- Neutron losses vs reactor operating time, 916
- NFPN, 791
 fission-product removal, 899
 removal by zinc drossing, chemistry of, 824

- Noble fission product removal, 823
Nonferrous metals, 770
Nuclear aspects of coolants, 837
Nuclear calculations, 874
 for various power splits, results of, 876
 results, 903
Nuclear properties of various reactor coolants, 839
- Off-gas system, 899
Open arrangements, 834
Orifice, 861
Oxidation, concurrent, of U, Zr, and Mg from Bi, 733
- Pa²³³, 713
Parametric study, 901
Pilot plant equilibrium experiments, 809
Piping, 849
Plant arrangement, 889
Plutonium, 725
Polonium, 705
 removal, 826
Power level, in the blanket, 871
Precipitation, of Fe-Cr alloy in high velocity cold leg test section, 763
Preheating, 855
Pressure measurement, 859
Pressure transmitters, 860
Primary inert gas system, 895
Process control, of fused chloride process, 817
Process design, data for, 809
Processing to reduce radiation hazard, 820
Protactinium losses, 886
Pumping power requirements, 840
Pumps, 843
Pyrometallurgical processing, 734
- Rapid oxidation, 767
Rates of precipitation, 750
Raw water system, 896
Reaction rates, 811
Reactivity effects, 713
Reactor and pressure vessel assembly, 933
 cell cooling, 895
 cost, 906
 heating and cooling system, 893
 room cooling, 896
 savings vs reflector thickness, 907
Reduction of UO₂ by Mg in Bi, 733
Reference design, selection of, 883, 911
specifications, 887, 918
Reflector, 715
Reflector savings, of U²³⁵-Bi cores moderated by graphite, 716
Relative cost vs slurry-to-graphite ratio, 910
 vs thorium concentration, 910
Relative fuel costs vs blanket power, 882, 883
Repair techniques, 858
Results of optimization, 881
- Salt corrosion, 773
Salts, 730
Samarium in the blanket, 873
Sampling, 856
Shield cooling, 895
Shielding, 719
Sight ports, 852
Single-fluid LMFR, critical fuel concentration vs thorium concentration, 905
 critical fuel concentration vs slurry-to-graphite volume ratio, 905
 conversion ratio vs slurry-to-graphite ratio, 904
 relative energy costs, 912
 relative fuel costs including chemical processing, 914
 summary of capital investment, 926
 summary of direct construction costs, 922
Single-fluid nuclear calculations, summary, 902
Single-fluid reactor cost, estimated, 907
 design, 900
Slurries, engineering studies of, 738
 thorium compound, 741
Slurry behavior, under conditions of reactor blanket operation, 739
Slurry preparation, electrolytic method, 736
Solubility, mutual, of uranium zirconium in bismuth, 727
 of combination of elements in bismuth, 726
 of corrosion products in bismuth, 726

- of Fe, Cr, Ni, and Mn in bismuth, 728
- of Fe in Bi alloys, 745
- of fission products in bismuth, 726
- of plutonium and uranium in bismuth, 724
- of steel components and inhibiting additives in bismuth, 744
- of titanium in bismuth, 728
- of uranium and thorium in bismuth, 724
- of uranium in bismuth, 729
- Solutes, distribution between $MgCl_2$ - $NaCl$ - KCl , 805
- Solution properties, 731
- Solution rate tests, 749
- Solutions, physical properties of, 731
- Stainless steels, 743, 854
- Startup heating system, 894
- Static tests, 744
- Steel composition and heat treatment, effect of, 748
- Steels, corrosion testing on, 751
 - radiation effects on, 768
 - reactions with Bi solutions, 746
- Study groups, work of, 704
- Surface reactions, 745
 - of zirconium, titanium, and magnesium, 746
- System design, 888
- System preparation, 852

- Tantalum, 770
- Temperature measurement, 862
- Ternary salt, 803
- Theory and experiment, comparison of, 805
- Thermal breeder, 711
- Thermal convection loop, 753
 - data, summary, 754
 - tests at BNL, 751
- Thief-type sampler, 856
- Thorium²³², 722
- Thorium, 706, 725
 - amortization charges, 879
 - bismuth blanket, preparation, 736 ff
 - bismuthide, chemical composition, 734
 - crystal chemistry, 734
 - burnup, 879
 - costs, 909
 - oxide, 741
 - Time study, 911
 - results of, 915
 - Turbine generator plant, 898
 - Two-fluid LMFR, chemical processing
 - costs, 884
 - inventory volumes in, 879
 - summary of direct construction costs, 924
 - Two-fluid reactor, design, 866
 - general description, 866
 - general specifications, 867
 - Typical reactor coolants, physical properties, 840
 - U^{233} , 706
 - U^{235} , 706
 - U^{238} , 706
 - Unit energy costs, 929
 - Uranium, 703, 723
 - Uranium-graphite reactions, 775
 - Uranium removal column, with four removal stages, 816
 - U-Zr-Bi ternary system: liquidus curves at 375, 400, and 425°C, 729

 - Values of μ , the gamma absorption coefficient, 839
 - Valves, 848
 - Variable fuel cost, 916
 - Volatile fission product removal, 795

 - Xenon, and iodine adsorption on graphite and steel, 796
 - and iodine removal, 795
 - concentration, changes in, 718
 - in the blanket, 872

 - Zirconium, 725
 - as a corrosion inhibitor, 722